

## RLT-P40 Rust Preventative Oil

### DESCRIPTION:

RLT-P40 is a volatile film anti-rust oil. It has good water displacement and low taste, and has good isolation effect on salt fog. After the volatile of rust proof oil, it can leave a layer of oil film on the metal surface, which has excellent long-term rust prevention ability. It can be used for 18 months when the anti rust is indoors.

### PHYSICAL AND CHEMICAL PROPERTIES:

Test Item	Test Method	Quality Index
Appearance	Visual inspection	transparency liquid
Flash ( opening)°C	GB/T3536	>78
Specific Gravity(15/4°C)		0.8
Aridity	SH/T 0063	Oily
Corrosion test (copper, 100°C, 3h), ≤2 grade	GB/T5096	Qualified
Salt spray test (45# steel sheet), >24h	SH/T0081	Qualified
Viscosity (40°C, cSt)		2.4
Humid test (hr)	SH/T0081	120

### APPLICATION:

Suitable for all kinds of indoor or outdoor mechanical anti-rust and metal products packaging anti-rust.

### USAGE:

1. After cleaning and drying the workpiece, apply oil by dipping, brushing or spraying at room temperature.
2. The parts after unpacking can be used directly without degreasing.
3. The precision parts should be sealed after being oiled to prevent dust adhesion.

### ATTENTION:

1. Use at room temperature, avoid open fire to prevent fire.
2. The oil tank should be capped when it is not used to avoid oil pollution.
3. The metal parts must be cleaned and dehydrated before being transferred into this product.