



Technical Data Sheet

RLT-AW2000 Aluminum Wheel Cutting Fluid

DESCRIPTION

RLT-AW2000 is designed for operation of aluminum wheel.

RLT-AW2000 can satisfy the requirement of high speed and general cutting working of aluminum wheel.

RLT-AW2000 can improve the surface finishing obviously, extend the tool life and improve the surface finish of the work piece.

RLT-AW2000 is suitable for CNC machine center, multi-purpose combined tool machine and centralized cooling system.

FEATURES AND BENEFITS

- Excellent lubricity
- Good bio-stability
- Good anti-rust properties
- Long service life

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Appearance (Neat)	Clear colorless liquid
Appearance (2.5% in DI water)	Clear colorless liquid
Specific Gravity @ 24°C	0.965
PH, (Neat)	Not Applicable
PH, (10% in DI water)	8.36
Solubility in water	100% miscible

USAGE

1. Dilute by water from 1:10 to 1:30.
2. Use deionized water would be better.
3. Supplement timely while using.

APPLICATIONS

RLT-AW2000 is specially designed for operations on aluminum wheel.

STORAGE

- Store inside warehouse
- Store out of direct sunlight
- Avoid water collecting on barrel top

Disclaimer: Information provided by this TDS including specifications and applications is based on tests and data supplied by Fanchu companies or any of our collaborated companies, which are believed to be correct and reliable at the time of data update. However, Fanchu companies and any of our collaborated companies make no warranty or responsibility, express or implied, of any kind regarding products, performance or applications, as operation conditions and application environments are beyond our control. Users are herewith expressly requested to conduct test to determine the suitability of our products before use.