

Technical Data Sheet



RLT-RX104 Silicone Emulsion

DESCRIPTION:

RX104 is a 50% solid content modified silicone oil with stable quality, the color is milk white and light blue, it can be stored for longer than 2 years without layering.

RX104 is widely used for die casting release agent. It is superior to conventional silicone fluids when the finished parts are subsequently to be painted, printed, coated or bonded. An outstanding release effect is even obtained when extremely small amounts of the release agent are used. The result is an easy, accurate reproduction of every surface detail of the molded article. RX104 exhibits excellent film forming properties.

RX104 is suitable for the production of release agents with temperature resistance 220-350°C.

PRODUCT DATA

Test Item	Test Standard	Test Value
Appearance	Visual Inspection	clear, colorless to yellowish
Kinematic Viscosity (25 °C)	Viscosity Tester	900 - 1500 mm ² /s
Dynamic Viscosity (25 °C)	Viscosity Tester	800 - 1400 mPa.s
Refractive Index (25 °C)	Refractometer	approx. 1.4640
Density at 25 °C	DIN 51757	0.912 g/cm ³
Volatility (230 °C, 2h, 5g sample)	High Temperature Oven Test	< 1.5 %

PRODUCT FEATURE

1. Excellent performance of lubricity.
2. Does not affect post-processing performance (such as Painting, electroplating,printing) of castings.
3. Excellent resistance to high temperature, no residues, no smoke on the die and molded part.

APPLICATIONS

It can be used in many kinds of metal die casting, such as Aluminum, Magnesium, Zinc alloy die casting. It is especially suitable for applications with high die temperatures and for the production of big, heavy and complicated parts.

PACKING SIZE

To be packed in plastic barrel of 20kg, 200kg, 1000IBC